


6W


Basic parameter

Warranty	5 years
Wattage	6W
Size	L120*W22*H80mm
Cutout	/
Installation	Magnetic Track
IP Rating	IP20
Beam Angle	24°/38°
Fitting Material	Aluminum+pc
Finish Color	Sand White /Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	ERP




Light parameters

Led Brand&Type&CCT	OSRAM 3030 6V 1W
Ra	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	90.36Lm/W
Led chip numbers	6PCS
Lumen	3000K: 469.6Lm 4000K: 480.31Lm 5000K:490.67Lm



Driver parameter

Driver Brand & Type	LTECH
Input	DC 48V
Output	DC9-42V 150mA
Powerrating	6W
Power Factor	/
Typical Efficiency	≥94%
Ta/Tc	45℃/75℃
Surge	1000V




Packaging parameter

Quality(pcs/Ctn)	48
N.W.(g*pcs)	193*48
G.W. (Kg/Ctn)	10.67
Inner Box(mm)	L82*W28*H135
Outer Box(CM)	L28.5*W26*H25
Volume(M³/Ctn)	0.018525
N.W : (g/pcs)	213
N.W : (g/pcs)	193

12W


Basic parameter

Warranty	5 years
Wattage	12W
Size	L236*W22*H80mm
Cutout	/
Installation	Magnetic Track
IP Rating	IP20
Beam Angle	24°/38°
Fitting Material	Aluminum+pc
Finish Color	Sand White/Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	ERP




Light parameters

Led Brand&Type&CCT	OSRAM 3030 6V 1W
Ra	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	88.59Lm/W
Led chip numbers	12PCS
Lumen	3000K: 999.6Lm 4000K: 1020.1Lm 5000K:1045.3Lm



Driver parameter

Driver Brand & Type	LTECH
Input	DC 48V
Output	DC9-42V 300mA
Powerrating	12W
Power Factor	/
Typical Efficiency	≥94%
Ta/Tc	45℃/75℃
Surge	1000V




Packaging parameter

Quality(pcs/Ctn)	30
N.W.(g*pcs)	314*30
G.W. (Kg/Ctn)	10.6
Inner Box(mm)	L85*W28*H249
Outer Box(CM)	L44*W26*H19
Volume(M /Ctn)	0.021736
N.W : (g/pcs)	352
N.W : (g/pcs)	314

18W


Basic parameter

Warranty	5 years
Wattage	18W
Size	L350*W22*H80mm
Cutout	/
Installation	Magnetic Track
IP Rating	IP20
Beam Angle	24°/38°
Fitting Material	Aluminum+pc
Finish Color	Sand White /Sand Black
Working Temperature	-10℃~40℃s
Product Standards	IEC(or EN)60598-1
Certification	ERP




Light parameters

Led Brand&Type&CCT	OSRAM 3030 6V 1W
Ra	≥90
CCT	3000K 4000K 5000K
Luminaire Efficacy	101.9Lm/W
Led chip numbers	18PCS
Lumen	3000K:1527.1Lm 4000K: 1556.4Lm 5000K:1586.41Lm



Driver parameter

Driver Brand & Type	LTECH
Input	DC 48V
Output	DC9-42V 400mA
Powerrating	18W
Power Factor	/
Typical Efficiency	≥94%
Ta/Tc	45℃/75℃
Surge	1000V



Packaging parameter

Quality(pcs/Ctn)	24
N.W.(g*pcs)	443*24
G.W. (Kg/Ctn)	12.5
Inner Box(mm)	L82*W28*H365
Outer Box(CM)	L38*W34.5*H19
Volume(M³/Ctn)	0.024909
N.W : (g/pcs)	493
N.W : (g/pcs)	443